



## SERIE SINGLE

Basic semi-automatic stretch wrappers that wrap palletized loads with stretch film, net or macro-perforated film. The cutting of film and attachment to the pallet must be performed manually, all other operations are completely automated and programmable.

# STRECH WRAPPING SEMIAUTOMÀTIC COMPARATIVE TABLE

PERFORMANCE	SINGLE MID	SINGLE ECO	FENIX
Output	Manual	Manual	Manual
Pallet Maximum Sizes	1200 x 1000 mm	1200 x 1000 mm	1200 x 1000 mm
Load Maximum Height	2400 mm	2400 mm	2400 mm
Load Maximum Weight	2000 kg	1500 kg	2000 kg
<b>TURNTABLE</b>			
Turning Speed	14 RPM	14 RPM	14 RPM
Diameter	1650 mm	1650 mm	1650 mm
Height	82 mm	82 mm	82 mm
<b>PERFORMANCE FEATURES</b>			
Load Fastening (tie)	Manual	Manual	Manual
Film Cutting	Manual	Manual	Manual
Remote Control	-	-	-
Wrapping Programs	4	2	4
Film Tension Control	Mecatens	Brake on Reel	Mecatens
Pre-stretching Relation	-	-	-
Platform Turning Speed Control	✓	Optional	✓
Reel Carriage Speed Control	✓	Optional	✓
Film Maximum Width	500 mm	500 mm	500 mm
Film Capacity (Reel Diameter)	260 mm	260 mm	260 mm
<b>OPTIONS</b>			
Column Height	2900 mm	-	3500 mm
Platform Width	2400 mm	-	2400 mm
Platform Access Ramp	✓	✓	✓
Pit Frame for floor embedding	✓	✓	✓
Powered Pre-stretching	✓	-	✓
Integrated Scale	✓	-	✓
Dispensador de cobertura superior	MANUAL	MANUAL	MANUAL
Largest Maximum Load Weight	Max. 3000 kg	Max. 3000 kg	Max 3000 kg
Raised Legs on Base	✓	✓	✓
Powered Top Platen to stabilise load	-	-	✓
Powered Rollers on Platform	-	-	✓
Double Reel Support	✓	✓	✓
Hotwelding on load	-	-	-
Adaptation to different working environments and temperatures	✓	✓	✓
Stainless Steel version	✓	✓	✓
ANFID Tape Dispenser	-	-	✓
RFID Label Reader	✓	-	✓
Jumbo Reels	-	-	-
<b>WEIGHT &amp; SIZES</b>			
Weight	415 kg	400 kg	440 kg
Sizes	L	2859 mm	2859 mm
	A	1650 mm	1650 mm
	H	2555 mm	2555 mm
<b>UTILITIES</b>			
Electrics		230V II+T	
Consumption	1 kW/h	1 kW/h	1 kW/h