



## CASE ERECTOR BE

Automatic equipment for the formation of boxes type RSC and closed inferior by means of adhesive tape, glue paper or hot glue. Manually adjustable quickly and easily to work with different carton formats. Designed to be integrated into production lines, they are robust and reliable machines, ideal for high levels of production

# CASE ERECTOR BE TECHNICAL DATASHEET

MODEL		BE2	BE3	BE4	BE5
Max. output		17 cases/min	15 cases/min	12 cases/min	9 cases/min
Maximum case sizes (Outer sizes)	L	450 mm	650 mm	750 mm	850 mm
	W	310 mm	410 mm	510 mm	610 mm
	H	500 mm	600 mm	650 mm	700 mm
Minimum case sizes (Outer sizes)	L	210 mm	300 mm	300 mm	400 mm
	W	120 mm	200 mm	300 mm	300 mm
	H	100 mm	130 mm	160 mm	200 mm
Admitted box types		RSC / HSC / FEFCO / 0200/0201			
Available bottom sealing types		Tape, Hotmelt Glue, Gummed Paper			
<b>UTILIES</b>					
Pneumatic working Pressure		6 Bar	6 Bar	6 Bar	6 Bar
Air consumption		30 l/cases	30 l/cases	40 l/cases	40 l/cases
Electrical power		230/400V III+N+T			
Maximum electrical consumption		1 Kw			
<b>MACHINE DATA</b>					
Magazine capacity*		150 uni	150 uni	150 uni	150 uni
Working height		550-750 mm	550-750 mm	550-750 mm	550-750 mm
Approx. weight		375 kg	425 kg	575 kg	650 kg
Dimensions (tape version)	L	2410 mm	2537 mm	2637 mm	2737 mm
	W	1980 mm	2278 mm	2486 mm	2836 mm
	H	1742 mm	1781 mm	1981 mm	1960 mm

\*Orientative values. To be confirmed depending on the case type , sizes and selected bottom sealing.