



SERIE FENIX

Basic semi-automatic stretch wrappers that wrap palletized loads and are designed to be customized for different load types. The cutting of film and attachment to the pallet must be performed manually, all other operations are completely automated and programmable. We offer a wide variety of options and accessories to adapt to the needs of your product and work environment.

SEMIAUTOMÁTIC STRECH WRAPPING FENIX

PERFORMANCE

Output	Manual
Pallet Maximum Sizes	1200 x 1000 mm
Load Maximum Height	2400 mm
Load Maximum Weight	2000 kg

MAIN FEATURES

Load Fastening (tie)	Manual
Film Cutting	Manual
Remote Control	-
Wrapping Programs	4
Film Tension Control	Mecatens
Pre-stretching Relation	-
Platform Turning Speed Control	✓
Reel Carriage Speed Control	✓
Film Maximum Width	500 mm
Film Capacity (Reel Diameter)	260 mm

OPTIONS

Column Height	3500 mm
Platform Width	2400 mm
Platform Access Ramp	✓
Pit Frame for floor embedding	✓
Powered Pre-stretching	✓
Integrated Scale	✓
Dispensador de cobertura superior	Manual
Largest Maximum Load Weight	Max. 3000 kg
Raised Legs on Base	✓
Powered Top Platen to stabilise load	✓
Powered Rollers on Platform	✓
Double Reel Support	✓
Hotwelding on load	-
Adaptation to different working environments and temperatures	✓
Stainless Steel version	✓
ANFID Tape Dispenser	✓
RFID Label Reader	✓
Jumbo Reels	-

PLATFORM

Turning Device	Platform
Turning Speed	14 RPM
Diameter	1650 mm
Height	82 mm

WEIGHT & SIZES

Weight	440 kg	
Sizes	L	2585 mm
	W	1650 mm
	H	2651 mm

UTILITIES

Electrics	230V II+T
Consumption	1 kW/h